

The Coaxial Cable is designed to meet or exceed MIL-STD-810.



Specifications

Cable	Power at 400mhz	Typical Attenuation / 100ft
RG-213	450W	4.2 dB
RG-223	215W	8.2 dB
RG-58	135W	11.2 dB
RG-400	710W	9.0 dB
RG-316	200W	16.0 dB

Cable Options

	End 1 Cable
A	TYPE "N" Male (Plug)
B	BNC Male (Plug)
C	TNC Male (Plug)
D	SMA Male (Plug)
E	QMA Male (Plug)
F	TYPE "N" Female (Jack)
G	BNC Female (Jack)
H	TNC Female (Jack)
I	SMA Female (Jack)
J	QMA Female (Jack)

	End 2 Antenna Connector
a	TYPE "N" Male (Plug)
b	BNC Male (Plug)
c	TNC Male (Plug)
d	SMA Male (Plug)
e	QMA Male (Plug)
f	TYPE "N" Female (Jack)
g	BNC Female (Jack)
h	TNC Female (Jack)
i	SMA Female (Jack)
J	QMA Female (Jack)

	Cable Type
1	RG-213
2	RG-223
3	RG-58
4	RG-400
5	RG-316
6	LMR-195

	Cable Length
10	10' (3.04m)
25	25' (7.6m)
30	30' (9.14m)
50	50' (15.2m)
75	75' (22.9m)
100	100' (30.5m)
150	150' (45.7m)
200	200' (61m)
250	250' (76.2m)

****All information on this product and the product itself is the property of and is proprietary to Hascall-Denke.**

****Specifications are subject to change without prior notice.**

