

## COAXIAL CABLE

The Coaxial Cable is designed to meet or exceed MIL-STD-810.

### Specifications

**ELECTRICAL:**

Cable	Power at 400mhz	Typical Attenuation / 100ft
RG-213	450W	4.8 dB
RG-223	215W	12.0 dB
RG-58	135W	11.2 dB
RG-400	710W	9.0 dB
RG-316	200W	21.0 dB

### Cable Options

	End 1 Cable Connector
A	TYPE "N"
B	BNC
C	TNC
D	SMA

	End 2 Antenna Connector
a	TYPE "N"
b	BNC
c	TNC
d	SMA

	Cable Type
1	RG-213
2	RG-223
3	RG-58
4	RG-400
5	RG-316

	Cable Length
10	10' (3.04m)
25	25' (7.6m)
50	50' (15.2m)
75	75' (22.9m)
100	100' (30.5m)
150	150' (45.7m)
200	200' (61m)
250	250' (76.2m)

**\*\*All information on this product and the product itself is the property of and is proprietary to Hascall-Denke.**

**\*\*Specifications are subject to change without prior notice.**



Made in the USA  
ISO 9001:2008 Certified  
(1Y26450)

P.O. Box 909, Palmetto, Florida 34220-0909  
Tel: 941-723-2833 • Fax: 941-723-1628  
www.hascall-denke.com